

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 June 2005 (23.06.2005)

PCT

(10) International Publication Number
WO 2005/057118 A1

(51) International Patent Classification⁷: **F28D 9/00**,
F28F 3/08, 9/22

Ramlösa (SE). **DAHLBERG, Tomas** [SE/SE]; Brommagatan 18, S-254 38 Helsingborg (SE).

(21) International Application Number:
PCT/SE2004/001714

(74) Agent: **LARSEN, Stig**; Allégatan 28, S-234 32 Lomma (SE).

(22) International Filing Date:
24 November 2004 (24.11.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03 03307-3 10 December 2003 (10.12.2003) SE

(71) Applicant: **SWEP INTERNATIONAL AB** [SE/SE];
Bävergatan 9, P.O. Box 105, S-261 22 Landskrona (SE).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **ANDERSSON, Sven** [SE/SE]; Råby 2040, S-242 92 Hörby (SE). **ANDRE, Hans** [SE/SE]; Härlemans Allé 20, S-256 57

[Continued on next page]

(54) Title: PLATE HEAT EXCHANGER



(57) Abstract: A plate heat exchanger comprising plates (21, 31) interconnected by soldering and adapted to exchange heat between a high and a low temperature fluid may be designed to improve the cooling of the parts of the plates located near inlets (3) for the high temperature fluid by providing separate fluid channels (23, 26) in pairs of plates (21, 31) guiding low temperature fluid, said separate channels (23, 26) at least partly surrounding said inlets (3) for the high temperature fluid.



WO 2005/057118 A1



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*